

Product data sheet

Characteristics

M8650B0C0E6C7A1A

ION8650 meter 64MB, 9S/29S/36S, 277VAC
60Hz, Full comm No I/O, password



Main

Range	PowerLogic
Device short name	ION8650B
Product or component type	Energy and power quality meter

Complementary

Power quality analysis	<p>conforming to IEC 61000-4-30: class S power quality measurement conforming to IEC 61000-4-15 flicker transient capture magnitude harmonic up to the 40th conforming to EN 50160: ed. 4 compliance report harmonic distortion voltage sag and swell detection programmability (logic and math functions) up to the 63rd harmonic</p>
Device application	<p>Demand and power factor control Energy pulsing and totalisation Co-generation and IPP monitoring Instrument transformer correction Load curtailment Tariff metering Equipment monitoring and control</p>
Type of measurement	<p>Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power per phase Reactive power total Reactive power per phase</p>
Supply voltage	<p>120...277 V AC 47...63 Hz 120...480 V AC 47...63 Hz</p>
Network frequency	60 Hz
[In] rated current	<p>5 A 1 A 2 A</p>
Type of network	3P

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	3P + N 1P + N
Power consumption in VA	24 VA
Maximum power consumption in VA	33 VA
Display type	FSTN transfective LCD
Form designation	9S 3-element 4 36S 2½-element 4 29S 2½-element 4
Sampling rate	1024 samples/cycle
Measurement current	0.001...24 A
Input type	Current 0.01...20 A (impedance 0.05 Ohm)
Measurement voltage	57...277 V AC phase to neutral 100...480 V AC phase to phase
Number of inputs	0
Measurement accuracy	Current 0.1 % Voltage 0.1 % Power 0.1 % Power factor 0.1 % Frequency 0.001 Hz Energy 0.1 %
Accuracy class	Class 0.2S energy conforming to IEC 62053-23 Class 0.2 energy conforming to ANSI C12.20 Class 0.2S energy conforming to IEC 62053-22
Number of outputs	2 pulse
Communication port protocol	DNP3 at 300...115200 bauds ION at 300...115200 bauds Ansi C12.18 at <= 19200 bauds IEC 61850 ed. 2 at 10/100 Mbit/s TCP/IP at 10/100 Mbit/s DLMS at 300...115200 bauds Modbus at 57600 bauds TCP/IP at 300...57600 bauds DNP3 at 10/100 Mbit/s ION at 10/100 Mbit/s ModemGate Modbus RTU, slave at 300...115200 bauds Modbus TCP, slave at 10/100 Mbit/s EtherGate
Communication port support	RJ45: Ethernet SUB-D 9: RS485/RS232 Terminal block: RS485 Infrared RJ11: modem
Time synchronisation protocol	GPS: Truetime/Datum IRIG-B
Data recording	Revenue logs Alarms Event logs Historical logs Time stamping Data logs Sag and swell logs Harmonics logs GPS synchronisation
Transmission rate	10/100 Mbit/s 300...57600 bauds <= 19200 bauds 57600 bauds 300...115200 bauds
Memory capacity	64 MB
Web services	Robust security logs Alarm notification by e-mail Port addressing user designed Web server
Ethernet service	Enable/disable serial ports SNMP-Traps and SYSLOG Enable/disable Ethernet protocols

Tamperproof of settings	Hardware lock by jumper Protected by access code
Compatibility code	ION8650B

Environment

Electromagnetic compatibility	Electrostatic discharge immunity test conforming to IEC 61000-4-2 Conducted RF disturbances conforming to IEC 61000-4-6 Immunity to impulse waves conforming to IEC 61000-4-12 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted and radiated emissions B conforming to CISPR 22
Mounting mode	Socket-mounted
Mounting support	Enclosure door
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP65 front face: IP51 back:
Relative humidity	5...95 %
Pollution degree	2
Ambient air temperature for operation	-40...85 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...3000 m
Standards	ANSI C12.1 IEC 62052-11
Width	178 mm
Depth	237 mm
Height	178 mm
Net weight	7 kg

Packing Units

Package 1 Weight	4.500 kg
Package 1 Height	26.000 cm
Package 1 width	28.000 cm
Package 1 Length	44.000 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov